

Guide Specification: Emergency shut off valve for installation under gasoline dispensing units. Incorporates a replaceable shear section and a heat sensitive fusible link assembly. Valve can be manually operated to facilitate dispenser maintenance and incorporates a 3/8" test port. Closing poppet assembly is positioned out of the fuel flow path to minimize pressure drop. The A0060 utilizes a standard three boss mounting arrangement. Available in single poppet and double poppet configurations.

Model No.	Description	Inlet	Outlet	Weight	A	B
A0060-002	1½" Single Poppet	Female	Male	4.0 lbs.	6.9"	2.2"
A0060-003	1½" Single Poppet	Female	Female	4.0 lbs.	6.4"	1.7"
A0060-015	1½" Single Poppet	Female BSPT	Male BSPT	4.0 lbs.	6.9"	2.3"
A0060-016	1½" Single Poppet	Female BSPT	Female BSPT	4.0 lbs.	6.9"	2.3"
A0060-022	1½" Double Poppet	Female	Male	4.2 lbs.	8.0"	3.3"
A0060-023	1½" Double Poppet	Female	Female	4.2 lbs.	6.9"	2.3"
A0060-025	1½" Double Poppet	Female BSPT	Male BSPT	4.2 lbs.	8.0"	3.3"
A0060-026	1½" Double Poppet	Female BSPT	Female BSPT	4.2 lbs.	6.9"	2.3"

BSPT versions available with bottom external threads. To order, add an "S" to the end of the variant number. Shear valves also available with U-bolt kit. Add a "U" to the end of the variant number.


Optional Items:

Model No.	Description	Outlet	Weight
492938	1½" Replacement Top; 1 Poppet	Male	1.4 lbs.
492939	1½" Replacement Top; 1 Poppet	Female	1.4 lbs.
493885	1½" Replacement Top; 1 Poppet	Female BSPT	1.4 lbs.
493886	1½" Replacement Top; 1 Poppet	Male BSPT	1.6 lbs.
493887	1½" Replacement Top; 2 Poppets	Male	1.6 lbs.
493888	1½" Replacement Top; 2 Poppets	Female	1.6 lbs.
493889	1½" Replacement Top; 2 Poppets	Male BSPT	1.6 lbs.
493890	1½" Replacement Top; 2 Poppets	Female BSPT	1.6 lbs.
492963	Fusible Link Kit		
A0065-001	Stabilizer Bar Mounting Kit for A0060		

Materials

Body: Cast Iron
Spring: Stainless Steel
Seal: Viton®

Viton® is a registered trademark of DuPont Dow Elastomers.



Emco Wheaton Retail Corporation

2300 Industrial Park Drive • Wilson, North Carolina 27893
252-243-0150 • 252-243-4603 (fax) • www.emcoretail.com

Form V-1000
Date 10/09