

# A0075/A0078 Ball Float

## A0075 Ball Float

The Emco Wheaton A0075 Ball Float Valves are designed to restrict product flow in the event of a UST overfill. The A0075 meets EPA requirements for a slow down device and incorporates a stainless steel ball and aluminum tube.

| Model No. | Tube Diameter | Tube Length | Overall Length | Bleed Hole | Weight    |
|-----------|---------------|-------------|----------------|------------|-----------|
| A0075-001 | 2"            | 4.75"       | 9.52"          | .125"      | 1.13 lbs. |
| A0075-002 | 2"            | 9.62"       | 14.39"         | .125"      | 1.70 lbs. |
| A0075-004 | 2"            | 8.00"       | 12.77"         | .125"      | 1.50 lbs. |
| A0075-006 | 2"            | 6.87"       | 11.64"         | .062"      | 1.37 lbs. |
| A0075-010 | 2"            | 18.00"      | 22.77"         | .125"      | 2.75 lbs. |
| A0075-013 | 2"            | 13.75"      | 18.52"         | .125"      | 2.25 lbs. |
| A0075-015 | 2"            | 15.75"      | 20.75"         | .125"      | 2.51 lbs. |
| A0075-017 | 2"            | 17.75"      | 22.52"         | .125"      | 2.77 lbs. |
| A0075-319 | 3"            | 19.75"      | 24.52"         | .125"      | 6.45 lbs. |



■ CARB Executive Order  
G-70-97-A

Steel tubes and custom lengths are available upon request.

## A0078 Ball Float with Extractor Cage

The Emco Wheaton A0078 combination Ball Float and Extractor Valve Cage meet the EPA requirements for a 30 minute warning device. The A0078 incorporates a stainless steel ball and aluminum tube.

| Model No. | Tube Diameter | Tube Length | Overall Length | Bleed Hole | Weight    |
|-----------|---------------|-------------|----------------|------------|-----------|
| A0078-008 | 2"            | 8.75"       | 13.52"         | .0625"     | 2.87 lbs. |
| A0078-015 | 2"            | 15.75"      | 20.52"         | .0625"     | 3.78 lbs. |
| A0078-020 | 2"            | 20.50"      | 25.27"         | .0625"     | 4.89 lbs. |
| A0078-308 | 3"            | 8.00"       | 12.77"         | .0625"     | 2.77 lbs. |
| A0078-312 | 3"            | 12.13"      | 16.27"         | .0625"     | 4.82 lbs. |
| A0078-318 | 3"            | 18.13"      | 22.27"         | .0625"     | 6.36 lbs. |



Steel tubes and custom lengths are available upon request.